

TERRATORQUE HELICAL ANCHORS AND HELICAL PILING PRODUCT CATALOG

INTRODUCTION

TerraTorque offers quality helical anchors and helical piling to the construction industry. Our products are available in solid square shaft (type TSA), hollow round shaft (type TRP) and hollow square shaft (type TSP) configurations. Standard series TSA solid square anchors are available in 1-1/2", 1-3/4" and 2" square sizes. Standard series TRP hollow round piles are available in 2-7/8" OD up to 12-3/4" OD and series TSP hollow square piles are available in 2-1/2" to 5"sizes. Custom sizes per customer request can be easily accommodated. Type TSA, TRP and TSP are suitable for compression and tension applications in a wide variety of soils and load capacities. The TSA series anchors are also utilized for our TPL pipeline anchor sets.

For pipeline buoyancy control, our TPL series pipeline anchors are offered as a complete pipeline anchor set. This product is commonly used on pipelines worldwide to provide buoyancy control for onshore pipelines. The TPL series anchor sets are also utilized offshore to provide pipeline stabilization solutions, span rectification and buoyancy control. The sets are designed to meet the project specifications and are supplied complete with anchors, extensions, saddles, corrosion protection and fasteners.

The TSA solid square shaft anchors utilize a high strength steel coupling to bolt the sections together to reach the required depth. The TRP round pipe and TSP square tubing incorporate a welded sleeve/coupling and high strength bolts to connect sections together. Our helices are machine pressed to form a true helical shape that does not auger or dig its way into the soil, but slowly screws into the soil with minimal soil disturbance.

The lead section has helical plates welded to the shaft. The lead may be a single helix or multiple helices, depending on the site soil conditions and the design loads. If additional helices are required, a helical extension may be used. Plain extensions are then added to the assembly as required until the lead sections penetrate into the bearing strata of the soil and the installation torque requirements are achieved.

Our materials are fabricated in our ISO 9001-2008 certified factory using new materials and industry accepted fabrication techniques. Our on premises hot dip galvanizing is available for all our products.

Worldwide shipping is no problem. Our experienced shipping team can ship our products worldwide to your destination quickly, efficiently and economically.

Common material configurations are provided in this catalog. We can also readily manufacture products to meet the specific requirements of our customers. In addition to what we present in our catalog we also have the flexibility, upon request, to provide custom designed product with:

- 1. Larger or smaller size square shafts or round shafts
- 2. Any diameter pipe for helical shafts as specified by a project requirement or customer
- 3. Any wall thickness of pipe for helical piling shafts as specified by project requirement or customer
- 4. Higher grades of pipe for helical piling shafts as specified by project requirements or customer
- 5. Wide range of component lengths
- 6. Various grades, thicknesses, diameters and quantities of helices
- 7. Stepped or transition piling / combination piles

TerraTorque, Inc. Labuan, Malaysia

Phone: +66 91 782 9491



TERRATORQUE FAMILY OF PRODUCTS

Our Product Line at a Glance:


Product	Description	Standard Sizes
TSA	Solid Square Shaft	1-1/2" to 2" Solid
	Helical Anchors	Square Bar
TPL	Pipeline Anchor Sets	1-1/2" to 2" Solid
	Utilizing TSA Anchors	Square Bar
TRP	Hollow Round Pipe	2-7/8" O.D. to
	Shaft Helical Piling	12-3/4" O.D pipe
TSP	Hollow Square Tubing	2-1/2" square to 5"
	Shaft Helical Piling	square tubing



TSA/TPL Solid Square Bar



TRP
Hollow Round Tubing/Pipe



TSP Hollow Square Tubing

Note: Above table indicates typical sizes. Custom sizes per customer requirements available on request. Shipping: Our experienced shipping team can ship our products worldwide quickly and economically

TerraTorque, Inc. Labuan, Malaysia

Phone: +66 91 782 9491



TERRATORQUE TUBULAR SQUARE SHAFT (TSP) PRODUCTS COMPONENT DIMENSIONS

Tubular Square Shaft (TSP) Dimensions


Square Tube Size	Wall Thickness inches	Coupling Bolt Diameter Inches
TSP20-25 (2")	0.250 (1/4")	0.75 (3/4")
TSP25-25 (2-1/2")	0.250 (1/4")	0.75 (3/4")
TSP30-25 (3")	0.250 (1/4")	0.875 (7/8")
TSP30-31 (3")	0.313 (5/16")	0.875 (7/8")
TSP40-25 (4")	0.250 (1/4")	1.25 (1-1/4")
TSP40-37 (4")	0.375 (3/8")	1.25 (1-1/4")
TSP40-50 (4")	0.500 (1/2")	1.25 (1-1/4")
TSP50-25 (5")	0250 (1/4")	1.50 (1-1/2")
TSP50-37 (5")	0.375 (3/8")	1.50 (1-1/2")
TSP50-50 (5")	0.500 (1/2")	1.50 (1-1/2")

TerraTorque, Inc. Labuan, Malaysia

Phone: +66 91 782 9491




TerraTorque TSP Tubular Square Shaft Helical Piling Typical Components




SQUARE TUBING SHAFT

0 0

PLAIN EXTENSION



HELICAL EXTENSION



LEAD SECTION SINGLE OR MULTIPLE HELIX

TerraTorque, Inc. Labuan, Malaysia

Phone: +66 91 782 9491



TerraTorque TSP Tubular Square Shaft Helical Piling

Tubular Square Shaft (TSP) Data

Product Specifications		
Tubing Dimensions	2" to 5" Square Tubing	
Tubing Material Standard	A500 Gr B or equivalent	
Tubing Strength, Min. per Standard	Yield: 46KSI; Tensile: 50 KSI*	
Material Condition	New, hot rolled, seamless	
Standard Length, Leads, Extensions	3/5/7/10 (feet)	
Coupling	Welded	
Coupling Material	Steel tube or Cast Steel	
Helix Material	Q345B per GB/T3274-2007	
Helix Strength, Min. per Standard	Yield: 50KSI; Tensile: 68KSI**	
Helix Diameter Sizes, Standard	8/10/12/14 (inches)	
Helix Thicknesses, Standard	0.375, 0.500, 0.625 (inches)	
Welding	All welds are 0.25" Fillet, minimum	
Fasteners	Gr 8.8; Yield: 95KSI; Tensile: 120KSI	
Surface Options	Bare steel, Galvanizing, Painted	

^{*}Higher strength shaft tubing available on request

Ordering Information

We provide quick turn-around on all piling and anchor orders. For load transfer to piling, we also provide pile caps that utilize either rebar, plates, or underpinning assemblies. Pile caps can also be custom fabricated to customer requirements.

If your pile design is already established, simply contact us at info@terratorque.com and indicate the details of your pile requirements. We will provide you a price and delivery quotation for the piling you require.

If your pile design is undetermined, we can assist you in developing the helical pile design to meet your project specifications. Simply contact us at info@terratorque.com and we can help you determine the piling configuration to meet your project specifications.

TerraTorque, Inc. Labuan, Malaysia

Phone: +66 91 782 9491

^{**}Higher strength helix material available on request